








# ELECTROMAGNETIC LOCKS

## Indoor GEM Series

New Style Mounting Plate Design							
	GEM-300	GEM-600	GEM-800	GEM-1200	GEM-D600	GEM-D800	GEM-D1200
<b>Model</b>							
<b>Voltage</b>	12/24 VDC Auto selectable	12/24 VDC Auto selectable	12/24 VDC Auto selectable	12/24 VDC Auto selectable	12/24 VDC Auto selectable	12/24 VDC Auto selectable	12/24 VDC Auto selectable
<b>Current</b>	500 mA/12 VDC 250 mA/24 VDC	500 mA/12 VDC 250 mA/24 VDC	500 mA/12 VDC 250 mA/24 VDC	500 mA/12 VDC 250 mA/24 VDC	500 mA/12 VDC 250 mA/24 VDC	500 mA/12 VDC 250 mA/24 VDC	500 mA/12 VDC 250 mA/24 VDC
<b>Holding Force (lbs)</b>	300	600	800	1200	600 (per lock)	800 (per lock)	1200 (per lock)
<b>Magnet Dimensions</b>	7 7/8"L x 1 7/16"W x 7/8"D 200 x 36 x 22.2 mm	9 13/16"L x 1 3/4"W x 1"D 250 x 44 x 26 mm	10 7/16"L x 1 15/16"W x 1 1/8"D 265 x 49 x 29 mm	10 1/2"L x 2 11/16"W x 1 9/16"D 267 x 68 x 40 mm	19 11/16"L x 1 3/4"W x 1"D 500 x 44 x 26 mm	20 7/8"L x 1 15/16"W x 1 1/8"D 530 x 49 x 29 mm	21"L x 2 11/16"W x 1 9/16"D 534 x 68 x 40 mm
<b>Housing</b>	Aluminum anodized (US28)	Aluminum anodized (US28)	Aluminum anodized (US28)	Aluminum anodized (US28)	Aluminum anodized (US28)	Aluminum anodized (US28)	Aluminum anodized (US28)
<b>Functional Options</b>	M	M, ML, TD, DS	M, ML, TD, DS, LD, BZ	M, ML, TD, DS, LD, BZ	M, ML, TD, DS	M, ML, TD, BZ	M, ML, TD, DS, BZ
<b>Standards &amp; Compliance</b>	NF S 61-937	UL 10B, UL 10C, ULC S104, NF S 61-937	UL 10B, UL 10C, ULC S104, NF S 61-937	UL 10B, UL 10C, ULC S104, NF S 61-937	UL 10B, UL 10C, ULC S104	UL 10B, UL 10C, ULC S104	UL 10B, UL 10C, ULC S104

**M:** Bond sensor & Bi-color status LED indicator **DS:** Door status sensor

**TD:** Relock time delay **BZ:** Door held open alarm **LD:** Large LED & Reset input **ML:** Bond sensor & Square LED