















CALL POINTS

	Break Plastic Glass Call Points			Resettable Call Points			
Model	CP-31-GP-UC 	CP-34GP-UC 	CP-34GPBZ-LB-UC 	CP-32G CP-33G 	CP-32G-LB 	CP-32GBZ-LB CP-33GBZ-LB 	CP-32GBZ-LB-ALM 
Switch Pole	Double pole	Quadruple pole	Triple pole	Double pole	Double pole	Double pole	Double pole
Contact Rating	5A 125/250 VAC	5A 125/250 VAC	5A 125/250 VAC	5A 125/250 VAC	5A 125/250 VAC	5A 125/250 VAC	5A 125/250 VAC
Buzzer	No	No	Yes	No	No	Yes	Yes
12/24 VDC input Terminal	No	No	Yes	No	No	No	No
Backlight	—	—	Blue/Green or Blue/Red illumination	—	Blue illumination	Blue illumination	Blue illumination
Case Colors							
Terminal Block Connector	No	No	No	CP-33G Only	No	CP-33GBZ-LB Only	No
Dimensions (mm)	87 x 87 x 55	87 x 87 x 55	87 x 87 x 55	91 x 87 x 53	91 x 87 x 53	91 x 87 x 53	91 x 87 x 53
Accessories	Plastic glass, Clear plastic cover, Test key	Plastic glass, Clear plastic cover, Test key	Plastic glass, Clear plastic cover, Test key	Resettable key, Clear plastic cover	Resettable key, Clear plastic cover	Resettable key, Clear plastic cover	Resettable key, Clear plastic cover, Bead cable tie