

# KEY SWITCHES

	ANSI Standard			European Standard				Narrow Stile
Model	KS-500	KS-700W	KS-750	KS-7510A	KS-800	KS-810	KS-860	KS-900
								
Switch Contact	SPDT	SPDT	SPDT, DPDT	SPDT	SPDT, DPDT	SPDT, DPDT	SPDT	SPDT, DPDT
Contact Rating	5A/125VAC	5A/125VAC	5A/125VAC	4A/125VAC	5A/125VAC	5A/125VAC	5A/125VAC	5A/125VAC
Switch Type	Momentary	Momentary Alternate (Maintained)	Alternate (Maintained)	Momentary	Alternate (Maintained)	Momentary	Momentary Alternate (Maintained)	Alternate (Maintained) Momentary (For KS-910)
Back Box	No	Optional	Optional	No	Optional	Optional	Optional	Optional
LED	No	No	Optional	No	Optional	Optional	Optional	Optional
Cylinder & Keys	Optional	Optional	Optional	Yes	Optional	Optional	Optional	Optional
Faceplate Material	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Dimensions	4 1/2" x 2 3/4" x 1 3/8" (114 x 69.7 x 35 mm)	4 1/2" x 2 3/4" x 1/8" (114 x 69.7 x 35 mm)	4 1/2" x 2 3/4" x 1/8" (114 x 69.7 x 35 mm)	86.3 x 86.3 x 47 mm	86.3 x 86.3 x 47 mm	86.3 x 86.3 x 47 mm	86.3 x 86.3 x 47 mm	109.5 x 52 x 37.5 mm