

# KEY SWITCHES

	ANSI Standard			European Standard				Narrow Stile	
Model	KS-500	KS-700W	KS-750	KS-7510A	KS-800	KS-810	KS-860	KS-900	KS-910
									
<b>Switch Contact</b>	SPDT	SPDT	DPDT	SPDT	SPDT, DPDT	SPDT, DPDT	DPDT	SPDT, DPDT	SPDT, DPDT
<b>Contact Rating</b>	5A/125VAC	5A/125VAC	5A/125VAC	4A/125VAC	5A/125VAC	5A/125VAC	5A/125VAC	5A/125VAC	5A/125VAC
<b>Switch Type</b>	Momentary	Momentary Alternate (Maintained)	Alternate (Maintained)	Momentary	Alternate (Maintained)	Momentary	Momentary Alternate (Maintained)	Alternate (Maintained)	Momentary
<b>Back Box</b>	No	Optional	Optional	No	Optional	Optional	Optional	Optional	Optional
<b>LED</b>	No	No	Optional	No	Optional	Optional	Optional	Optional	Optional
<b>Cylinder &amp; Keys</b>	No	Optional	Optional	Yes	Optional	Optional	Optional	Optional	Optional
<b>Faceplate Material</b>	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
<b>Dimensions</b>	4 1/2" x 2 3/4" x 1 3/8" (114 x 69.7 x 35 mm)	4 1/2" x 2 3/4" x 1/8" (114 x 69.7 x 35 mm)	4 1/2" x 2 3/4" x 1/8" (114 x 69.7 x 35 mm)	86.3 x 86.3 x 47 mm	86.3 x 86.3 x 47 mm	86.3 x 86.3 x 47 mm	86.3 x 86.3 x 47 mm	109.5 x 52 x 37.5 mm	109.5 x 52 x 37.5 mm