








# ACCESS CONTROL ACCESSORIES

## Power Transfer Door Loops (Surface Mount)

Model	Description	Length of Conduit	Model	Description	Length of Conduit
 <p>DL-200A-30 DL-200A-40 DL-200A-50</p>	<ul style="list-style-type: none"> <li>• Aluminum end caps</li> <li>• Armored stainless steel flex conduit</li> </ul>	<p>11 13/16" (300 mm) 15 3/4" (400 mm) 19 11/16" (500 mm)</p>	 <p>DL-350SP-40 DL-350SP-60</p>	<ul style="list-style-type: none"> <li>• Aluminum end caps</li> <li>• Armored spring steel flex conduit</li> </ul>	<p>15 3/4" (400 mm) 23 5/8" (600 mm)</p>
 <p>DL-200P-30 DL-200P-40 DL-200P-50</p>	<ul style="list-style-type: none"> <li>• Silver plastic end caps</li> <li>• Armored stainless steel flex conduit</li> <li>• Optional finishes: Black, White (For 500 mm length of conduit)</li> </ul>	<p>11 13/16" (300 mm) 15 3/4" (400 mm) 19 11/16" (500 mm)</p>	 <p>DL-370</p>	<ul style="list-style-type: none"> <li>• Aluminum end boxes</li> <li>• Armored stainless steel flex conduit</li> <li>• Silver finish</li> <li>• Patented</li> </ul>	<p>15 3/4" (400 mm)</p>
 <p>DL-330-40</p>	<ul style="list-style-type: none"> <li>• Aluminum end caps</li> <li>• Armored stainless steel flex conduit</li> </ul>	<p>15 3/4" (400 mm)</p>	 <p>DL-370-US40</p>	<ul style="list-style-type: none"> <li>• Aluminum end boxes</li> <li>• Armored stainless steel flex conduit</li> <li>• US 40 finish</li> <li>• Patented</li> </ul>	<p>15 3/4" (400 mm)</p>
 <p>DL-350-40 DL-350-46 DL-350-50 DL-350-60 DL-350-71 DL-350-85</p>	<ul style="list-style-type: none"> <li>• Aluminum end caps</li> <li>• Armored stainless steel flex conduit</li> </ul>	<p>15 3/4" (400 mm) 18 1/8" (460 mm) 19 11/16" (500 mm) 23 5/8" (600 mm) 27 15/16" (710 mm) 33 7/16" (850 mm)</p>			

# ACCESS CONTROL ACCESSORIES

Power Transfer Door Loops (Mortise Mount)		
Model	Description	Dimensions
 <b>DL-400</b>	<ul style="list-style-type: none"> <li>• Steel case</li> <li>• Nickel-plated steel flex conduit</li> </ul>	11 7/16" x 15/16" x 5/8" (290 x 24.5 x 16.3 mm)
 <b>DL-417ST</b>	<ul style="list-style-type: none"> <li>• Stainless steel case</li> <li>• Stainless steel flex conduit</li> <li>• For metal frames</li> </ul>	11 7/16" x 15/16" x 13/16" (290 x 24.5 x 20 mm)
 <b>DL-500</b> <b>DL-500MP</b>	<ul style="list-style-type: none"> <li>• Zinc alloy case</li> <li>• Stainless steel flex conduit</li> <li>• For wood frames</li> </ul>	11 1/2" x 1" x 11/16" (292 x 24.8 x 18 mm)











Power Transfer Door Loops with Terminal Boards		
Model	Description	Dimensions
 <b>DL-360TB</b>	<ul style="list-style-type: none"> <li>• Aluminum end boxes</li> <li>• Armored stainless steel flex conduit</li> <li>• Includes terminal boards</li> <li>• Patented</li> </ul>	Length of conduit 15 3/4" (400 mm)
 <b>DL-417ST-TB</b>	<ul style="list-style-type: none"> <li>• Stainless steel case</li> <li>• Stainless steel flex conduit</li> <li>• Includes terminal boards</li> <li>• For metal frames</li> </ul>	12 5/8" x 1" x 2 1/6" (320 x 25 x 53 mm)
 <b>DL-500-TB</b>	<ul style="list-style-type: none"> <li>• Zinc alloy case in ivory finish</li> <li>• Stainless steel flex conduit</li> <li>• Includes terminal boards</li> <li>• For wood frames</li> <li>• Patented</li> </ul>	12 5/8" x 15/16" x 2 3/16" (320 x 24.5 x 55 mm)

# ACCESS CONTROL ACCESSORIES

LED Indicator Ligtjs		
Model	Description	Faceplate Material
 TLM-100MTS	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• (Surface mount option <b>TLM-100</b>)</li> </ul>	Stainless steel
 TLM-300	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• (Surface mount option <b>TLM-300S</b>)</li> <li>• Push button included</li> </ul>	Zinc alloy
 TLM-400	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• (Surface mount option <b>TLM-400S</b>)</li> </ul>	Zinc alloy
 TLM-600N	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> </ul>	Stainless steel
 TLM-600-4	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• Push button included</li> </ul>	Stainless steel
 TLM-200	<ul style="list-style-type: none"> <li>• European size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• Optional back box available</li> </ul>	Stainless steel

Magnetic Contacts		
Model	Description	Operating Gap
 GMC-2071	<ul style="list-style-type: none"> <li>• Door status monitor</li> <li>• SPDT contact</li> <li>• Wire mounted</li> <li>• Aluminum alloy case</li> </ul>	Wood: 25 mm Iron: 5 mm
 GMC-2071-AR	<ul style="list-style-type: none"> <li>• Door status monitor</li> <li>• SPDT contact</li> <li>• Armored cable included</li> <li>• Wire mounted</li> <li>• Aluminum alloy case</li> </ul>	Wood: 34 mm Iron: 7 mm
 GMC-2031	<ul style="list-style-type: none"> <li>• Door status monitor</li> <li>• SPDT contact</li> <li>• Screw mounted</li> <li>• Plastic case</li> </ul>	Wood: 29 mm Iron: 18 mm

# ACCESS CONTROL ACCESSORIES

Door Latches		Door Control Modules		Rectifier Gadgets	
Model	Description	Model	Description	Model	Description
 <p><b>LS-1802GF</b></p>	<ul style="list-style-type: none"> <li>• Stainless steel latchbolt</li> <li>• Zinc alloy construction &amp; faceplate</li> <li>• For wood doors</li> </ul>	 <p><b>ILM-200</b></p>	<p><b>2 Door interlock Module</b></p> <ul style="list-style-type: none"> <li>• Controls the opening of 2 doors</li> <li>• Used in high security or confidential areas</li> </ul>	 <p><b>SM1224-1A-N</b></p>	<ul style="list-style-type: none"> <li>• Input voltage 12 to 24VAC/DC</li> <li>• Output voltage 1A/12VDC</li> <li>• Output status LED</li> </ul>
 <p><b>LS-2200</b></p>	<ul style="list-style-type: none"> <li>• Stainless steel latchbolt</li> <li>• Anti-friction roller bolt design</li> <li>• Aluminum alloy construction</li> <li>• Stainless steel faceplate</li> <li>• For wood doors</li> </ul>	 <p><b>DBR-200</b></p>	<p><b>Versatile Relay Module</b></p> <ul style="list-style-type: none"> <li>• DPDT changeover contacts</li> <li>• Relay rating 5A 24VAC/30VDC</li> </ul>	 <p><b>SM1224BZ-1A</b></p>	<ul style="list-style-type: none"> <li>• Input voltage 12 to 24VAC/DC</li> <li>• Output voltage 1A/12VDC</li> <li>• Output status LED</li> <li>• Built-in buzzer</li> </ul>
 <p><b>LS-3500/3600</b></p>	<ul style="list-style-type: none"> <li>• Stainless steel latchbolt</li> <li>• Easily reversible bolt</li> <li>• Round/Square faceplate option</li> <li>• For wood/hollow metal doors</li> <li>• Operates with knob/lever/thumb turn (Model LS-3600 operates with cylindrical knob/lever)</li> </ul>	 <p><b>FFP-1224-7A</b></p>	<p><b>Fire Alarm Relay Module</b></p> <ul style="list-style-type: none"> <li>• Fire alarm release module</li> <li>• For fail-safe/fail-secure devices</li> <li>• Relay rating 7A/30VDC</li> </ul>	 <p><b>CPP912</b></p>	<ul style="list-style-type: none"> <li>• Input voltage 12 to 32 VDC or 12 to 24 VAC</li> <li>• Prolonged solenoid life</li> <li>• Provides cooler strike operation</li> <li>• For fail-safe electric strikes</li> </ul>
				 <p><b>CPP1824</b></p>	<ul style="list-style-type: none"> <li>• Input voltage 24 to 33 VAC/DC</li> <li>• Prolonged solenoid life</li> <li>• Provides cooler strike operation</li> <li>• For fail-safe electric strikes</li> </ul>