








# ACCESS CONTROL ACCESSORIES




## Power Transfer Door Loops (Surface Mount)

Model	Description	Length of Conduit
 DL-200A	<ul style="list-style-type: none"> <li>Aluminum end caps</li> <li>Armored stainless steel flex conduit</li> </ul>	11 13/16" (300 mm) 15 3/4" (400 mm) 19 11/16" (500 mm)
 DL-200P	<ul style="list-style-type: none"> <li>Silver plastic end caps</li> <li>Armored stainless steel flex conduit</li> <li>Optional finishes: Black, White (For 500 mm length of conduit)</li> </ul>	11 13/16" (300 mm) 15 3/4" (400 mm) 19 11/16" (500 mm)
 DL-350	<ul style="list-style-type: none"> <li>Aluminum end caps</li> <li>Armored stainless steel flex conduit</li> </ul>	15 3/4" (400 mm)
 DL-350-SP	<ul style="list-style-type: none"> <li>Aluminum end caps</li> <li>Armored spring steel flex conduit</li> </ul>	15 3/4" (400 mm)
 DL-370	<ul style="list-style-type: none"> <li>Aluminum end boxes</li> <li>Armored stainless steel flex conduit</li> <li>Silver finish</li> <li>Patented</li> </ul>	15 3/4" (400 mm)
 DL-370-US40	<ul style="list-style-type: none"> <li>Aluminum end boxes</li> <li>Armored stainless steel flex conduit</li> <li>US 40 finish</li> <li>Patented</li> </ul>	15 3/4" (400 mm)

## Power Transfer Door Loops (Mortise Mount)

Model	Description	Dimensions
 DL-400	<ul style="list-style-type: none"> <li>Steel case</li> <li>Stainless steel flex conduit</li> </ul>	11 7/16" x 15/16" x 5/8" (290 x 24.5 x 16.3 mm)
 DL-417ST	<ul style="list-style-type: none"> <li>Stainless steel case</li> <li>Stainless steel flex conduit</li> <li>For metal frames</li> </ul>	11 7/16" x 15/16" x 13/16" (290 x 24.5 x 20 mm)
 DL-500	<ul style="list-style-type: none"> <li>Zinc alloy case in ivory finish</li> <li>Stainless steel flex conduit</li> <li>For wood frames</li> </ul>	11 1/2" x 1" x 11/16" (292 x 24.8 x 18 mm)

## Power Transfer Door Loops with Terminal Boards












Model	Description	Dimensions
 DL-360TB	<ul style="list-style-type: none"> <li>Aluminum end boxes</li> <li>Armored stainless steel flex conduit</li> <li>Includes terminal boards</li> <li>Patented</li> </ul>	Cable length 15 3/4" (400 mm)
 DL-417ST-TB	<ul style="list-style-type: none"> <li>Stainless steel case</li> <li>Stainless steel flex conduit</li> <li>Includes terminal boards</li> <li>For metal frames</li> </ul>	12 5/8" x 1" x 2 1/6" (320 x 25 x 53 mm)
 DL-500-TB	<ul style="list-style-type: none"> <li>Zinc alloy case in ivory finish</li> <li>Stainless steel flex conduit</li> <li>Includes terminal boards</li> <li>For wood frames</li> <li>Patented</li> </ul>	12 5/8" x 15/16" x 2 3/16" (320 x 24.5 x 55 mm)

# ACCESS CONTROL ACCESSORIES

LED Indicator Ligjts		
Model	Description	Faceplate Material
 <p><b>TLM-100MTS</b></p>	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>(Surface mount option <b>TLM-100</b>)</li> </ul>	Stainless steel
 <p><b>TLM-300</b></p>	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>(Surface mount option <b>TLM-300S</b>)</li> <li>• Push button included</li> </ul>	Zinc alloy
 <p><b>TLM-400</b></p>	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>(Surface mount option <b>TLM-400S</b>)</li> </ul>	Zinc alloy
 <p><b>TLM-600N</b></p>	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> </ul>	Stainless steel
 <p><b>TLM-600-4</b></p>	<ul style="list-style-type: none"> <li>• Narrow size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• Push button included</li> </ul>	Stainless steel
 <p><b>TLM-200</b></p>	<ul style="list-style-type: none"> <li>• European size</li> <li>• Red &amp; Green LEDs for lock status</li> <li>• Flush mounted</li> <li>• Optional back box available</li> </ul>	Stainless steel

Magnetic Contacts		
Model	Description	Operaing Gap
 <p><b>GMC-2071</b></p>	<ul style="list-style-type: none"> <li>• Door status monitor</li> <li>• SPDT contact</li> <li>• Wire mounted</li> <li>• Aluminum alloy case</li> </ul>	Wood: 25 mm Iron: 5 mm
 <p><b>GMC-2071-AR</b></p>	<ul style="list-style-type: none"> <li>• Door status monitor</li> <li>• SPDT contact</li> <li>• Armored cable included</li> <li>• Wire mounted</li> <li>• Aluminum alloy case</li> </ul>	Wood: 34 mm Iron: 7 mm
 <p><b>GMC-2031</b></p>	<ul style="list-style-type: none"> <li>• Door status monitor</li> <li>• SPDT contact</li> <li>• Screw mounted</li> <li>• Plastic case</li> </ul>	Wood: 29 mm Iron: 18 mm

# ACCESS CONTROL ACCESSORIES

Door Latches		Door Control Modules		Voltage Controllers	
Model	Description	Model	Description	Model	Description
 <p><b>LS-1802GF</b></p>	<ul style="list-style-type: none"> <li>Stainless steel latchbolt</li> <li>Zinc alloy construction &amp; faceplate</li> <li>For wood doors</li> </ul>	 <p><b>ILM-200</b></p>	<p><b>2 Door interlock Module</b></p> <ul style="list-style-type: none"> <li>Controls the opening of 2 doors</li> <li>Used in high security or confidential areas</li> </ul>	 <p><b>SM1224-1A</b></p>	<ul style="list-style-type: none"> <li>Input voltage 12 to 24VAC/DC</li> <li>Output voltage 0.3A/12VDC</li> <li>Voltage conversion board with black cover</li> </ul>
 <p><b>LS-2200</b></p>	<ul style="list-style-type: none"> <li>Stainless steel latchbolt</li> <li>Anti-friction roller bolt design</li> <li>Aluminum alloy construction</li> <li>Stainless steel faceplate</li> <li>For wood doors</li> </ul>	 <p><b>SM1228</b></p>	<p><b>Voltage Reduction Module</b></p> <ul style="list-style-type: none"> <li>Input voltage 13 to 28 VDC</li> <li>Output voltage 0.3A/12VDC</li> </ul>	 <p><b>SM1224-1A-N</b></p>	<ul style="list-style-type: none"> <li>Input voltage 12 to 24VAC/DC</li> <li>Output voltage 1A/12VDC</li> <li>Output status LED</li> </ul>
 <p><b>LS-3500/3600</b></p>	<ul style="list-style-type: none"> <li>Stainless steel latchbolt</li> <li>Easily reversible bolt</li> <li>Round/Square faceplate option</li> <li>For wood/hollow metal doors</li> <li>Operates with knob/lever/thumb turn (Model LS-3600 operates with cylindrical knob/lever)</li> </ul>	 <p><b>DBR-200</b></p>	<p><b>Versatile Relay Module</b></p> <ul style="list-style-type: none"> <li>DPDT changeover contacts</li> <li>Relay rating 5A 24VAC/30VDC</li> </ul>	 <p><b>SM1224BZ-1A</b></p>	<ul style="list-style-type: none"> <li>Input voltage 12 to 24VAC/DC</li> <li>Output voltage 1A/12VDC</li> <li>Output status LED</li> <li>Built-in buzzer</li> </ul>
		 <p><b>FFP-1224-7A</b></p>	<p><b>Fire Alarm Relay Module</b></p> <ul style="list-style-type: none"> <li>Fire alarm release module</li> <li>For fail-safe/fail-secure devices</li> <li>Relay rating 7A/30VDC</li> </ul>	 <p><b>SM1224-TBZ</b></p>	<ul style="list-style-type: none"> <li>Input voltage 12 to 24VAC/DC</li> <li>Output voltage 1A/12VDC</li> <li>Output status LED</li> <li>Built-in buzzer</li> <li>Anti-tailgate function</li> <li>Relock time delay</li> </ul>