

# ELECTROMECHANICAL LOCKING DEVICES

## Electric Locks





For Narrow Stile Doors				
	ML-210N-SW	ML-300-SW	ML-350M	ML-360M
Model				
Voltage	12 to 24 VDC/AC	12 to 24 VDC/AC	12 VDC, 24 VDC	12 VDC, 24 VDC
Monitoring	Lock status	Lock status	Lock status, Door status	Lock status, Door status
Installation Direction	Horizontal, Vertical	Vertical	Horizontal, Vertical	Horizontal, Vertical
Lock Mode	Reversible Fail-Safe/Fail-Secure	Reversible Fail-Safe/Fail-Secure	Fail-Safe	Fail-Safe
Preload Capability	—	—	500 lbs (227 kg)	500 lbs (227 kg)
Standards & Compliance	—	—	BS EN 14846 Fire tested to BSEN 1634-1: 2014 & BSEN 1363-1: 2012	BS EN 14846
Optional Mechanical Override	No	Yes (Optional cylinders & keys available)	No	No
Optional Model	—	—	ML-350 (24 VDC input, Non-monitored, NF S 61-937 compliant)	ML-360 (24 VDC input, Non-monitored, NF S 61-937 compliant)
Dimensions (mm)	210 L x 25 W x 44 D	250 L x 25 W x 44 D Backset: 30	200 L x 25 W x 39.5 D	200 L x 30.5 W x 45 D

# ELECTROMECHANICAL LOCKING DEVICES

## Electromechanical Push Bar

Preload Panic Exit Device		
Model	PBH-350	
		
Voltage	12 or 24 VDC	
Static Strength	1,500 lbs (680kg)	
Preload Capability	500 lbs (227kg)	
Lock Mode	Fail-Safe	
Housing	Aluminum anodized	
Dimensions	Bar	35 1/16" x 2 5/8" x 2 7/16" (890 x 66 x 61.5 mm)
	Strike	2 15/16" x 1 3/16" x 11/16" (75 x 30 x 17 mm)
Delayed Egress Function	Model	PBH-350DE
	Buzzer Alarm	95 dB
	Nuisance Delay	Field selectable 0, 1, 2, 3 seconds
	Exit Delay	Field selectable 15/30 seconds
	Functional Inputs	Emergency signal input Door ajar input

## Electromechanical Mortise Lock

ANSI Standard Mortise Lock		
Model	GML800	
		
Input Power	600mA/12VDC, 300mA/24VDC Field selectable 12/24 VDC	
Backset	2 3/4" (70 mm)	
Finish	Brushed stainless steel (US32D)	
Field Configuration	Changeable fail-safe/fail-secure operation Reversible latchbolt for right and left hand doors	
Optional Monitoring Outputs	Lock status, Request-to-Exit/Enter (Lever rotation), Door status	
Strike	4 7/8" x 1 1/4" , furnished with dust box	
Accessories	Cylinder & Keys	
Optional Lever Sets		
		
GEM800-SET with L811 Lever Option	GEM800-SET with L812 Lever Option	GEM800-SET with L814 Lever Option