

AUTOMATIC DOOR OPERATOR

The AD500 is an automatic swing door operator for a wide range of applications. It can be mounted on either side of the door header for pull or push action, and is suitable for single or double, inward or outward opening, left or right handed doors. It also offers numerous adjustable features and can be integrated with electric locks or access control systems to ensure all around safety.



OPB-500AD
Operation Controller

Easy, Convenient and Safe Access for Swing Doors

| | | |
|---------------------------------|--|--------------------------|
| Model | <p style="text-align: center;">AD500</p>  | |
| Application | Healthcare facilities, Office buildings, Homes, Business premises | |
| Features & Functions | <ul style="list-style-type: none"> • Non – handed • Push or pull side mounting • Integration with door mounted presence sensor (infrared technology) for safety • Backup battery input for emergency power supply • Power On/Off switch • Activation options: wall switches, card readers, microwave sensors • Adjustment of hold-up time, opening/closing speed, and opening angle • Integration with electric hardware and access control system • 4 Operation modes: Auto, Hold-open, Manual, Push & Go (PBT-020B-AD operation mode selector included) | |
| Technical Data | Power Input | 100 - 240 VAC, 3.2A Max. |
| | Door Weight | 60 - 150Kg |
| | Door Width | 47 1/4" (1200 mm) |
| | Compliance | CE, UL/CUL 325 |