

# Emergency Door Release Exit Device

## Dual Exit Units

### Convenient, Safe, Easy to install

#### Standard Features

- Combined exit button and emergency door release unit
- Double gang surface back box
- Horizontal or vertical installation
- Operating voltage 12/24 VDC
- Double pole switch
- Contact rating 5A/125 or 250VAC
- LED indicator
- Available in glass or resettable operating element



 <p><b>PBS-P430C1</b></p> <ul style="list-style-type: none"> <li>• Stainless steel button &amp; faceplate</li> <li>• Break glass element</li> </ul>	 <p><b>PBS-P430C2</b></p> <ul style="list-style-type: none"> <li>• Stainless steel button &amp; faceplate</li> <li>• Resettable</li> </ul>	 <p><b>PBS-P800C1</b></p> <ul style="list-style-type: none"> <li>• Plastic button</li> <li>• Break glass element</li> </ul>	 <p><b>PBS-P800C2</b></p> <ul style="list-style-type: none"> <li>• Plastic button</li> <li>• Resettable</li> </ul>
---	--	--	--

#### Replacements

 <p><b>PBS-286G</b> Replacement plastic case, 189.5 x 92 x 40mm</p>	 <p><b>P-PL-CP-31-K</b> Test key</p>	 <p><b>P-PL-CP-32-K</b> Resettable Key</p>
--	---	---

#### Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.