

Features

- ▶ Indoor & Outdoor Use - IP65 Waterproof
- ▶ Allows up to 99 access PINs.
- ▶ Maximum 20-digit-code password to avoid peeping or lockout for 30 seconds after entering invalid PINs for 5 times (The keypad doesn't beep sound during the period of time).
- ▶ Non-volatile memory stores PINs even when the power fails.
- ▶ Built-in anti-tamper switch
- ▶ AUX signal output: built-in additional output contact for other access control devices, such as alarm system or door status monitoring.
- ▶ Additional input for anti-tailgating function to ensure high security access control.
- ▶ Suitable for British standard or ANSI gang box for mortise mount.



Mortise Mount Installation



Specification

Operating Voltage	12-24 VAC/DC
Current Draw	Pull in: 220mA/12VDC ; Holding: 110mA/12VDC Pull in: 100mA/24VDC ; Holding: 50mA/24VDC
Input	1 contact for Request-To-Exit button
Output	1 relay (N.O./N.C./Com. Dry contacts)
PIN Length	4-8 digits (master code & PINs must be of the same length)
Relay Electric Rating	Max. 2A/30VDC
Memory Volume	99 PINs
Relay Strike Time	01-99 seconds, Toggle mode (00)
Dimensions	90 (W) x 134 (H) x 10/42 (D) mm

GIANNI INDUSTRIES, INC.