



# Door Control Modules

## Useful Gadgets

Item	Model	Specifications
	<b>ILM-300</b> Three-Door Interlocking Relay Module	<ul style="list-style-type: none"> <li>◆ Input Voltage 12 or 24VDC</li> <li>◆ Relay Rating: 3A@120VAC/30VDC</li> <li>◆ Dimensions: 73(L) x 63(W) mm</li> </ul>
	<b>ILM-200</b> Two-Door Interlocking Relay Module	<ul style="list-style-type: none"> <li>◆ Input Voltage 12VDC</li> <li>◆ Relay Rating: 3A@120VAC,24VDC</li> <li>◆ Dimensions: 73(L) x 63(W) mm</li> </ul>
	<b>DBR-200</b> Relay Module	<ul style="list-style-type: none"> <li>◆ Input Voltage: 12~24 VAC/DC</li> <li>◆ Current Draw: 50mA/12VDC</li> <li>◆ Relay Rating: 5A/250VAC , 5A/24VDC</li> <li>◆ Dimensions: 67(L) x 50(W) mm</li> </ul>
	<b>DBR-200-JP</b> Relay Module	<ul style="list-style-type: none"> <li>◆ Input Voltage: 12~24 VAC/DC</li> <li>◆ Current Draw: 50mA/12VDC</li> <li>◆ Relay Rating: 5A/250VAC , 5A/24VDC</li> <li>◆ Dimensions: 59(L) x 47(W) mm</li> </ul>
	<b>FFP-1224-7A</b> Fire Alarm Relay Module (Supports fail-safe/fail-secure devices)	<ul style="list-style-type: none"> <li>◆ Input Voltage: 12~24VDC</li> <li>◆ Output Voltage: 12~24VDC</li> <li>◆ Relay Rating: 7A/30VDC</li> <li>◆ Dimensions: 59(L) x 47(W) mm</li> </ul>
	<b>GPD-3015-PLUS</b> Voltage Distribution Board	<ul style="list-style-type: none"> <li>◆ DC voltage averagely distributed to five output contacts</li> <li>◆ Each contact with "PPTC" re-settable fuse protection based on the dynamic equilibrium of energy.</li> <li>◆ Dimensions: 70 (L) x 60 (W) mm</li> </ul>

### Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original customer. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.