

Proximity Keypad System

Standalone DG Series

DG-300 Illuminated Prox Keypad



Standard Features



- Backlit keys for better visibility and operation in the dark
- 3 Access modes: Card **only**, Card **or** Card, and Card **with** Code
- Multi-colored LED and built-in buzzer for status programming feedback
- Door sensor input for anti-tailgating operation to ensure higher security access control
- Logical memory prevents duplicated card setting
- Dual relays to control door lock and other security devices
- Keypad tamper lockout
- Non-volatile memory protects programmed information in case of power loss
- Built-in tamper switch



Specifications

Models	Voltage	Current	Prox Cards/ Tokens	PIN Code Digits	Inputs	Outputs	Reader Frequency	Reader Range	Reader Housing
DG-300EM	12 to 24 VAC/DC	90mA Pull-in, 70mA Holding at 12VDC; 60mA Pull-in, 50mA Holding at 24VDC	1000 + 10	4 digits	2 REX inputs 1 Door sensor input	2 Relays (NC/COM/NO) 1A/30VDC, 0.5A/125VAC	125KHz	10 cm	Plastic ABS

Dimensions



Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.